



- Compact Design
- Durable Anodized Aluminum
- Various Element Grades Available
- Ideal Point of Use Filter



Our 315A, 360A, and 370A filters are designed for demanding, high efficiency filtration. They are versatile enough to use on compressed air/gas lines, instrument airlines, CNG service, as well as other gaseous applications. The coalescing grade 70C element is an ideal fuel gas filter. For service with heavy particulate contaminants an "LSS" screen may be slipped into the inner diameter of the 360A and 370A for added filtration. See the "Pleated Elements for Compressed Gas Service" file. For fuel gas service the brass petcock should be replaced with a stainless steel plug.

HOUSING MODEL	315A	360A	370A
Port Size (NPT)	1/8" or 1/4"	1/4" or 1/2"	1/2"
Drain Type	Petcock	Manual	Manual
Maximum Temperature (°F)	200	200	200
Maximum Pressure (psig)	250	250	250
Principle Dimensions: (inches)			
Center Of Port To Head	0.39	0.61	0.61
Head	1.57	2.44	2.44
Overall Length	4.45	6.30	10.28
Filter Element Codes: (3)			
Disposable Element	12-32-□	25-64-□	25-178-□
Stainless Steel Element	SS-12-32-□	SS-25-64-□	SS-25-178-□
PEL Element	PEL-12-32-□	PEL25-64-□	PEL25-178-□
Pleated (for Particulate)	PT-12-32-□	25-64-□PL	25-178-□PL
Materials Of Construction (2):			
-Head	AL	AL	AL
-Bowl	AL	AL	AL
-Internals	Nylon	Nylon	Nylon
-Seals	Buna-N	Buna-N	Buna-A
-Others	Brass	Brass	Brass
Optional Items:			
Mounting Bracket	MB315	MB360	MB360
Bowl Guard	-	-	-
Viton Seal Set	GV315	GV360	GV360
DPI Kit	-	-	-
<b>Model w/ Differential Pressure Indicator</b>		<b>360AI</b>	<b>370AI</b>