


Series 740KF High Flow Filter Cartridges



FEATURES, ADVANTAGES AND BENEFITS

Series 740KF High Flow Filter Cartridge puts an extraordinary amount of surface area into a single cartridge. This results in the following:

- ◆ High loading capacity for long life and lower cost filtration.
- ◆ Fewer cartridges for fewer change-outs and lower labor cost.
- ◆ Fewer seals, reduced risk of bypass resulting in high quality filtration.
- ◆ Extremely low disposal costs, less than a tenth of some cartridges.

Double O-ring seals in a variety of material options means:

- ◆ Extremely low risk of bypass for high quality fluids.
- ◆ No loose parts to assemble for easy installation, thus less labor cost.
- ◆ No springs and caps to lose reduces the risk of bypass.
- ◆ Broad chemical compatibility for many applications.
- ◆ Convenient handle for easy manual or mechanical removal.

APPLICATIONS

Prefilters or Final Filters for:

- Acids and bases
- Amines
- Carbon beds
- Completion fluids
- Deep wells
- Desalination
- DI resins
- EDM Fluids
- Glycol
- Groundwater clean-up
- Laundry water
- Machine coolants
- Makeup water
- Organic solvents
- Photo chemicals
- Plating solutions
- RO membranes
- Storm Water
- UF membranes
- Wastewater
- Waterflood
- Workover fluids

MATERIALS OF CONSTRUCTION

Filter Media:

Meltblown polypropylene microfiber filter media provides high particle removal efficiency for high quality filtration with broad chemical compatibility.

No silicone is intentionally used in materials of construction or in manufacturing.

The raw materials composing these filters are FDA compliant according to CFR Title 21.

O-rings:

Model Number	Material
7010	FDA Buna N (standard)
7011	Ethylene Propylene Rubber
7012	PTFE Encapsulated Silicone
7013	FDA Silicone
7014	Fluoroelastomer

PERFORMANCE DATA

Loading Capacity

Model Number	743KF	744KF	745KF	746KF	747KF	748KF	749KF
Pounds at 40 gpm	13.7	13.7	13.7	14.1	14.6	13.4	15.4
Kilograms at 9 cu m/hr	6.2	6.2	6.2	6.4	6.6	6.1	7.0

Loading: The data above shows typical loading capacities of the different micron rated filters. Loading capacity is determined by challenging a filter with a dispersion of silica test dust in water at the recommended flow rate. Pressure drop is monitored and testing is terminated at 50 psid (3.4 bar). The loading capacity reported is the dry weight gain of the bag.

Particle Removal Efficiency (microns)

Model Number	743KF	744KF	745KF	746KF	747KF	748KF	749KF
Efficiency @99%	2	5	10	15	25	40	70
Efficiency @95%	1.1	2.5	8	9	13	24	43
Efficiency @90%	0.9	1.7	6	8	10	19	35
Efficiency @75%	0.7	1.5	3.5	6	8	13	24
Efficiency @50%	<0.7	1.1	1.5	4.0	4.5	8	14

Efficiency: The Series 740KF High Flow Filter Cartridges are rated using a silica test challenge in water at 40 gpm (9 cu m/hr). The results reported are typical initial efficiencies taken within ten minutes of the start of the test.

Clean Pressure Drop Versus Flow Rate (psid)

Model Number	743KF	744KF	745KF	746KF	747KF	748KF	749KF
Δp @ 20 gpm	0.5	0.2	0.1	0.1	0.1	0.10	0.07
Δp @ 40 gpm	1.0	0.5	0.4	0.2	0.2	0.19	0.16
Δp @ 60 gpm	1.3	0.6	0.5	0.4	0.4	0.30	0.24
Δp @ 80 gpm	1.8	0.8	0.7	0.5	0.5	0.40	0.32

Pressure Drop: The Series 740KF High Flow Filter Cartridges have low initial pressure drop (Δp) in water as the table indicates. The table does not include the pressure drop of the vessel.

OPERATING CONDITIONS

Maximum Operating Temperature	160° F (70° C)
Recommended Flow (in water)	40 gpm(9 cu m/hr)
Suggested Maximum Flow (in water):	
743KF	60 gpm (14 cu m/hr)
744KF – 749KF	80 gpm (18 cu m/hr)
Suggested Maximum Differential Pressure:	
743KF – 749KF	50 psid (3.4) bar

Disposal

Disposal of used filter bags must comply with applicable federal, state and local laws and regulations.

PRODUCT SPECIFICATIONS

Model Number	Micron Rating Initial Efficiency	Part Number	Length	Outer Diameter	Cartridges per Case
743KF	2 micron @ 99%	70-0708-1347-5	39 in (100 cm)	6.5 in (16.5 cm)	1
744KF	5 micron @ 99%	70-070-8-1348-3			
745KF	10 micron @ 99%	70-0708-1349-1			
746KF	15 micron @ 99%	70-0708-1350-9			
747KF	25 micron @ 99%	70-0708-1351-7			
748KF	40 micron @ 99%	70-0708-1352-5			
749KF	70 micron @ 99%	70-0708-1353-3			

226 O-Ring: inside diameter, 2 inches (5 cm); thickness, 0.14 inches (0.35 cm)

WARRANTY

Seller warrants its equipment against defects in workmanship and material for a period of 12 months from date of shipment from the factory under normal use and service and otherwise when such equipment is used in accordance with instructions furnished by Seller and for purposes disclosed in writing at the time of purchase, if any. Any unauthorized alteration or modification of the equipment by Buyer will void this warranty. Seller's liability under this warranty shall be limited to the replacement or repair, F.O.B. point of manufacture, of any defective equipment or part which, having been returned to the factory, transportation charges prepaid, has been inspected and determined by the Seller to be defective.

THIS WARRANTY IS IN LIEU OF ANY OTHER WARRANTY, EITHER EXPRESSED OR IMPLIED, AS TO DESCRIPTION, QUALITY, MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE OR USE, OR ANY OTHER MATTER. Under no circumstances shall Seller be liable to Buyer or any third party for any loss of profits or other direct or indirect costs, expenses, losses or consequential damages arising out of or as a result of any defects in or failure of its products or any part or parts thereof or arising out of or as a result of parts or components incorporated in Seller's equipment but not supplied by the Seller.



a 3M company

Cuno Incorporated

400 Research Parkway
Meriden, CT 06450, U.S.A.
Tel: (800) 243-6894
(203) 237-5541
Fax: (203) 630-4530
www.cuno.com