



"A leading worldwide supplier of high efficiency filters for a variety of industries and applications."

SIGHT GLASS

We offer four standard sizes of sight glass housings which are based upon our Pyrex / SS filter assemblies. These units provide a caged Pyrex bowl to monitor tank or boiler liquid levels safely. The compact model SG117 is especially suited as a flow monitor. All the units utilize a double open ended glass bowl which is "sandwiched" between two stainless steel end plates. Our design eliminates the cumbersome external bolts which is normal on many other brands. We feel our design simplifies installation and service.



Features:

- Caged Pyrex Bowl For Safety
- One Tie Rod Makes Service Quick And Simple

Applications:

- Level Indicator
- Flow Indicator
- Four Standard Sizes

TECHNICAL INFORMATION

Housing Model	SG117	SG127	SG137	SG147
Port Size (NPT)	1/4"	1/4"	1/4"	1/4"
Maximum Pressure (psig)	100	100	100	100
Maximum Temperature (°F)	212	212	212	212
Internal Volume (cc)	26	36	105	255
Principle Dimensions: (inches)				
Head Diameter	1.57	1.57	2.20	2.20
Overall Length	3.07	3.82	4.65	9.13
Removal Clearance	2.46	2.76	3.54	8.03
Materials Of Construction:				
Head, Base & Internals	316L Stainless Steel	316L Stainless Steel	316L Stainless Steel	316L Stainless Steel
Bowl	Pyrex	Pyrex	Pyrex	Pyrex
O-Rings	Viton	Viton	Viton	Viton
Accessories:				
Buna-N Seal Set	BNSG117	BNSG117	BNSG137	BNSG137
EPDM Seal Set	GESG117	GESG117	GESG137	GESG137
Kalrez Seal Set	KZSG117	KZSG117	KZSG137	KZSG137
Viton Seal Set (Standard)	GVSG117	GVSG117	GVSG137	GVSG137